



ORDER NO.  
IWPA-4-20-X-XXX-XX

1/8" DIA SENSOR (IN 1/32")	SHEATH LENGTH IN INCHES 3" 6" OR 12" LONG	FITTING XX=NONE 1/4" 3/8" OR 1/2"
RESISTANCE IN K OHM	CABLE LENGTH IN INCHES 96/144"	
INTERNAL WET PROBE ASS'Y (ARMORED CABLE)		

19	1	P45-0609Z4	POLY ZIP BAG W/ WRITING SURFACE 6 x 9 x 4M ZIP
18	1	MM-1814	INSTALLATION INSTRUCTION
17	1	C80-M2-202C	CONNECTOR 2 CONDUCTOR MALE
16	1	R95-9/32-9/16	RUBBER GROMMET 9/32 ID 9/16 OD Buna N
15	1	MM-6400	PART NO. LABEL TAPE 1/2" BLK ON YELLOW (A20-6311)
14	1	C54-A-5/32	ARMORED CABLE 5/32 ID 303 ST ST (ANAMET) 460613-0076
13	1	MM-8561	VINYL TUBING 1/4" ID 7/16" OD 3/32" WALL CUT 3" LONG CLEAR (T98-8-14)
12	1	MM-3768	CRIMP SLEEVE TUBING ST #304 .437 ID .5 OD .6" LONG (T94-RD-500-14)
11	1	MM-8640	FITTING 1/4" COMP 1/4" NPT (FERRULE LOOSE) MODIFIED (F48-68C-4-4)
10	1	MM-8630	COMPRESSION INSERT BRASS CDA 360 3/8" DIA (B80-12-R)
9	1	MM-5980	1/8" PROBE BUSHING (3/8" DIA BLACK ACETAL) (P70-AC-6-B)
8	1	W80-18-00	22 GAUGE WIRE 2" LONG STRIP 1/4 X 1/4"
7	1	S44-300-125	SHRINK TUBING 1/8" BLACK 100'
6	1	T97-TTI-S18	TEFLON TUBING .042 ID .066 OD 1.3" LONG
5	1	W84-TF-26-R	WIRE TEFLON TFE 26 AWG 19/38 RED
4	1	T97-TTI-S18	TEFLON TUBING .042 ID .066 OD 1.3" LONG
3	1	T26-20K	THERMISTOR NEG COEFF 20K (FENWAL) 135-203LAG-J01
2	1	MM-8517	CONNECTING TUBE .250 DIA 304 ST (T94-RD-25-16)
1	1	MM-8518	SENSOR TUBE 304 ST ST SEAMLESS .125 OD .085 W (T94-RD-125-85)
ITEM	Q	PART #	DESCRIPTION

**CHD PRODUCTS INC**

MATERIAL:  
FINISH:

N8779 HWY X WATERTOWN WI 53094 USA  
TEL (920)261-5799 FAX(920)261-1350

FRAME SIZE 10 X 6.5"  
1 X SCALE (SF 1)  
H. WIEDER 25 JULY 2021

TOLERANCE  
.00 + - .010"  
.000 + - .005"  
.0000 + - .001"

WATER CORE SENSOR  
DWG NO. PC-1800-A